

LINEAR-24 ELITE



5 R149 00HR PL 122

30 R149 00HR PL 1252 (E9)

ELITE

Measuring just 40mm in height, the Linear range represents the very best in slimline auxiliary high beam driving lights. By utilising a combination of highly efficient 3W LEDs and vacuum-metallised wide optics, to deliver a perfectly tuned beam pattern for everyday road use, the 24 Elite boasts 18,000 raw lumens, with 1 lux reaching just under 600m with a 64 degrees spread of light. Dual-output functionality allows for the UNECE reference number to be reduced, in markets requiring a low E-mark reference number, made possible through addition of the Linear E-Mark Cap (sold separately).



SEE MORE. GO FASTER. GO SAFER.



LINEAR-24 Elite

- Combination of highly efficient 3W 'premium bin' LEDs
- Vacuum-metallised optics deliver wide spread of light
- Flexible mounting options anti-theft mounting brackets included
- Lower E-Mark avaliable via a E-Mark cap
- Sleek, low profile design facilitates installation
- Electronic thermal management
- Designed & manufactured in the UK

MOUNTING OPTIONS





(Anti-theft fasteners included)

(Centre Mount kit sold seperately)









LAZER LAMPS LTD, Units 1+2, Harlow Mill Business Centre, Riverway, Harlow, Essex. CM20 2FD. UK Tel: +44(0)1992 677374 | Email: saleslolazerlamps.com | Web: www.lazerlamps.com

		_
E-MARK REF (W/O EMARK CAP WITH EMARK CAP)	2x30 2x17.5	
VOLTAGE RANGE	10V - 32V	
RAW LUMENS (W/O EMARK CAP WITH EMARK CAP)	18,000 7,740	
BEAM PATTERN	Wide	
BEAM DISTANCE (0.25LX) (W/O EMARK CAP WITH EMARK CAP)	1126m 712	
# HIGH POWER LEDS	24	
POWER CONSUMPTION (W/O EMARK CAP WITH EMARK CAP)	188W 38W	
CURRENT DRAW [†] (W/O EMARK CAP WITH EMARK CAP)	14.4A 2.6A	
LED LIFE	50,000 Hrs*	
WEIGHT	2000g	





* LED Manufacturers Specifications †At 14.4 Volts

Horizontal: 64º / Vertical: 15º (2% of peak)



